

**Amendments to the Claims:**

The listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

**Claim 1 (currently amended):** An endoscope comprising a flexible catheter probe having a plurality of lumens, a handle provided at the proximal end of the probe, an optical system provided in at least one optical system lumen of the catheter probe, at least one working lumen for a surgical instrument and a control element which is fixed to the distal end of the probe or in the proximity thereof for bending the end of the probe and is guided movably in the axial direction at the probe,

characterised in that

- the optical system [(6)] which projects beyond the proximal end of the catheter probe [(1)] is guided movably in a flexible tube [(2)];
- the tube [(2)] is elastically resilient in its longitudinal direction and is fixedly connected at a fixing location [(3)] to the optical system [(6)]; and
- the distal end of the optical system [(6)] is pressed by the tube [(2)] against a translucent cover [(7)] which closes the distal end [(4)] of the optical system lumen [(5)].

**Claim 2 (currently amended):** An endoscope according to claim 1,  
~~characterised in that wherein~~ the fixing location [[(3)]] is provided at the proximal end [[(8)]] of the tube [[(2)]].

**Claim 3 (currently amended):** An endoscope according to claim 1,  
~~charaeterised in that wherein~~ provided at the proximal end [[(9)]] of the optical system [[(6)]] is a connecting portion [[(10)]] which is connectable to an illumination device and/or to an ocular.

**Claim 4 (currently amended):** An endoscope according to ~~one of claims 1 to 3~~  
~~characterised in that claim 3, wherein~~ the fixing location [[(3)]] is provided at the connecting portion [[(10)]].

**Claim 5 (currently amended):** An endoscope according to ~~one of claims 1 to 4~~  
~~characterised in that claim 1, wherein~~ the flexible tube [[(2)]] is arranged outside the handle [[(12)]].

**Claim 6 (currently amended):** An endoscope of ~~one of claims 1 to 5~~  
~~characterised in that claim 1, wherein~~, at its proximal end, the catheter probe [[(1)]] is mounted rotatably to the handle [[(12)]] in a rotary bearing [[(14)]] through which the control element [[(13)]] is displaceably guided.

**Claim 7 (currently amended):** An endoscope according to claim 6,  
~~wherein characterised in that~~ a releasable fixing device [[(15)]] for the catheter probe [[(1)]] is provided on the rotary bearing [[(14)]].

**Claim 8 (currently amended):** An endoscope according to claim 6,  
~~wherein or claim 7 characterised in that~~ the rotary bearing has a manually  
actuable rotary portion [[(38)]] which is non-rotatably connected to the catheter  
probe [[(1)]].

**Claim 9 (currently amended):** An endoscope according to ~~one of claims~~  
~~1 to 8 characterised in that claim 7, wherein~~ the control element [[(13)]] is passed  
through the fixing device [[(15)]].

**Claim 10 (currently amended):** An endoscope according to ~~one of~~  
~~claims 1 to 9 characterised in that claim 7, wherein~~ the proximal end of the  
control element [[(13)]] is passed through the fixing device [[(15)]].

**Claim 11 (currently amended):** An endoscope according to ~~[[one of~~  
~~claims 1 to 10 characterised in that claim 1, wherein~~ the catheter [[(1)]] has a  
balloon [[(17)]] to which a dilation medium can be fed by way of a balloon lumen  
[[(18)]] in the catheter probe [[(1)]].

**Claim 12 (currently amended):** An endoscope according to ~~one of~~  
~~claims 1 to 11 characterised in that claim 1, wherein~~ a guide wire [[(11)]] can be  
guided through a guide wire lumen [[(19)]] which extends from the distal end  
[[(20)]] of the probe to an exit opening [[(21)]] in the catheter [[(22)]], the exit  
opening being behind the balloon [[(17)]].

**Claim 13 (currently amended):** An endoscope according to ~~one of~~  
~~claims 1 to 12 characterised in that claim 9, wherein~~ the control element [[(13)]]

is arranged in a flexible support tube [[(23)]] which is arranged in a control lumen [[(25)]] of the catheter probe [[(1)]] and terminates at a given spacing from the distal end [[(20)]] of the probe, wherein the given spacing corresponds approximately to the length of a distal portion [[(24)]] of the probe, which is to be bent over by the control element [[(13)]].

**Claim 14 (currently amended):** An endoscope according to ~~one of claims 1 to 13 characterised in that claim 9, wherein~~ the control element [[(13)]] is fixed to the distal end of the catheter probe [[(1)]] by a shrink tube [[(26)]] or by an adhesive [[(27)]].

**Claim 15 (currently amended):** An endoscope according to ~~one of claims 1 to 14 characterised in that claim 14, wherein~~ the support tube [[(23)]] is fixed at a fixing location [[(29)]] in the axial direction and the remaining portion of the support tube [[(23)]] is supported movably with respect to the inside wall of the control lumen [[(25)]].

**Claim 16 (currently amended):** An endoscope according to ~~one of claims 1 to 14 characterised in that claim 14, wherein~~ the fixing location [[(28)]] is provided at the distal end of the support tube [[(23)]] or in the proximity thereof.

**Claim 17 (currently amended):** An endoscope according to ~~one of claims 1 to 16 characterised in that claim 1, wherein~~ the surgical implement is

removable from the at least one working lumen [[(29)]] or is incorporated or integrated into the catheter probe [[(1)]].

**Claim 18 (currently amended):** An endoscope according to ~~one of claims 1 to 18 characterised in that claim 1, wherein~~ the catheter probe [[(1)]] is in the form of a disposable component.

**Claim 19 (currently amended):** An endoscope according to ~~one of claims 1 to 18 characterised in that claim 1, wherein~~ the catheter probe [[(1)]] is in the form of an injection ~~moulding~~ molded component or ~~extrusion~~ an extruded component.